

# **KDF Fluid Treatment (KDFFT) Research and Development Laboratory**

### **Analytical Report**

July 21, 2016

Omica Organics 706c E. Goode St. Quitman, TX 75783 Page 1 of 1

## Testing of Omica Organics Shower Filter for the Reduction of Free Chlorine to NSF Standard 177-2014

\*\*\*

This report details the steps used by the Research and Development Laboratory of KDF Fluid Treatment (KDFFT) in testing the efficiency of an Omica Organics shower filter for the removal of free chlorine from shower water. This protocol was established following the standards set by NSF International in NSF Standard 177-2014.

#### **Test Results**

Gallons	Flow Rate	Added Chlorine	Remaining Chlorine	% Chlorine Removed
15	2.52 gpm	1.90 mg/L	0.42 mg/L	78%
249	2.50 gpm	1.83 mg/L	0.12 mg/L	93%
902	2.47 gpm	1.91 mg/L	0.09 mg/L	95%
1563	2.49 gpm	1.82 mg/L	0.08 mg/L	96%

#### References

NSF/ANSI 177-2014. NSF International Standard for Shower Filter Systems. NSF International: Ann Arbor, MI

NOF IIILEITIALIOITAI. AITII AIDOI, IVII

Water Analysis Handbook, 2<sup>nd</sup> Edition. 1992. HACH Company. Loveland, CO 831 pages.

#### **Notes**

CONFIDENTIAL REPORT for sole use of Omica Organics.

Submitted by:

James T. Jeakle

Jan 7. Jenke

Mgr., Laboratory and Technical Services

Full signed lab report, with complete procedure methodology and testing equipment list, is available from Omica Organics upon request.